

**FORCE
INDUSTRIES
DIVISION**

American Solder & Flux Co., Inc. • 28 Industrial Boulevard • Paoli, PA 19301-0947 • (610) 647-3575 • FAX (610) 647-2375

PRODUCT INFORMATION

AMCO BLITZ

(228)

GENERAL CHARACTERISTICS AND USES

Amco BLITZ is an activated liquid flux for use with all common metals except aluminum. It is a specially formulated mixture of inorganic salts in water, with approximately 35-40% active ingredients. Conforms to Mil Spec AA51145C, Type I, Form B.

PHYSICAL DATA

- ◆ Clear liquid with slight yellow color.
- ◆ Specific Gravity: 1.378 @ 70 °F
- ◆ Weight per gallon: 11.6 lbs
- ◆ Shelf life: At least 1 year in unopened original container stored at room temperature.

APPLICATION

- ◆ Use with most tin/lead alloys.
- ◆ Residue is slightly corrosive - remove with hot water.
- ◆ May also be used with silver bearing solders for soldering stainless steel

RESIDUE

- ◆ Residue must be removed with hot water rinse

PACKAGING

- ◆ 1 pint bottles
- ◆ 1 gallon and 5 gallon jugs
- ◆ 50 gallon drum

While we believe the data presented herein is accurate and reliable, the data are not to be taken as a guarantee or representation of any kind for which Force Industries assumes legal responsibility. They are offered solely for your consideration, investigation and verification.