

**FORCE  
INDUSTRIES  
DIVISION**

American Solder & Flux Co., Inc. □ 28 Industrial Boulevard □ Paoli, PA 19301-0947 □ (610) 647-3575 □ FAX (610) 647-2375

---

## **PRODUCT INFORMATION**

### **AMCO 4918**

(672)

**GENERAL CHARACTERISTICS AND USES** - Amco 4918 is an environmentally designed oil and grease dissolving fluid. It is designed for maximum penetration on all common metals. Penetration is either by standing application or with rubbing onto the surface to be cleaned.

#### **PHYSICAL DATA – Water clear liquid**

- **Specific gravity: 0.800 @ 69° F.**
- **Weight per gallon: 6.66 pounds**
- **Flash point: 125° F , TCC**
- **FDA approved: 21 C. F. R. , section 178.3910, paragraph (b) , and others.**

#### **APPLICATION - Use as is**

- **Can be sprayed or dipped**
- **Can be used with mechanical devices in automated processes.**

#### **RESIDUE - Non-staining under normal conditions**

- **Need not be removed, once initial grime is removed and the surface is sufficiently cleaned.**

#### **PACKAGING - 5 gallon pails and 55 gallon non-returnable drums**

**PRECAUTION - If the ambient temperature falls below 40° F , the material will begin to solidify. The solution should be allowed to return to 62° F minimum, placed on a drum roller and rotated for 10 minutes before using. Performance is not impaired by this solidification.**